



STANDARD FEATURES

Stage	Integrated XY Stage
Travel	30mm to 300mm
Motor	Ironless Core Linear Motor
Feedback	Non-Contact Optical Encoder
Scale	Gold Tape Scale Optional: Near Zero CTE ZeroMet
Resolution	1Vp-p Analog Output (5nm with 4096 Interpolation) Digital Output Options: 5um, 1um, 0.5um, 0.2um, 100nm, 50nm, 20nm**, 10nm**, and 5nm** (* ** Reduced Speeds Apply)
Sensors	Integrated Home and End of Travel Limits
Bearings	High Precision Crossed Roller Bearings
Cables	High Flex, 10M Cycle, 3m Length
Structure	Anodized Aluminum 6061-T6 Optional: Stainless Steel
Environment	Standard Optional: Clean Room and Vacuum (10-6 Torr)
Temperature	0°C to 50°C
Humidity	10% to 80% Non-Condensing
Precision	6-D Nano Precision™ Test Methods

TRAVEL	LENGTH	WIDTH	HEIGHT	A (inch)	B (inch)	C	D	E	F	G	H	I	J	K
30	112	112	50	n/a	n/a	80	42	46	60	35	n/a	M4	M4 (4X)	M5 (4X)
60	125	125	60	4	3	100	75	46	60	35	n/a	M6 or 1/4-20	M4 (4X)	M5 (4X)
100	184	184	60	6	4	125	100	46	120	70	52	M6 or 1/4-20	M4 (4X)	M5 (6X)
150	225	225	60	6	6	175	125	120	170	70	52	M6 or 1/4-20	M5	M6
200	275	275	60	6	6	175	125	120	170	70	62	M6 or 1/4-20	M5	M6
250	400	400	100	12	8	350	250	170 & 225	275	100	96	M8 or 5/16-18	M6	M8 (6X)
300	500	500	100	12	8	350	250	170 & 225	275	100	96	M8 or 5/16-18	M6	M8 (6X)

* All units millimeters unless otherwise noted.

* All hole patterns centered on M5 dowel pin hole at center of stage.

ALIO INDUSTRIES PROPRIETARY INFORMATION
(Tel) 303.339.7500 - SALES@ALIOINDUSTRIES.COM - WWW.ALIOINDUSTRIES.COM



DRAWN	5/12/2012	TITLE	AI-CM-(TRAVEL)00-XY
NBROWN		SIZE	B
CHECKED		DWG NO	0010-08013
Tolerances: Surface Roughness: x.x ± .05 in [1.3 mm] x.xx ± .01 in [0.25 mm] x.xxx ± .005 in [0.13 mm] Angles ± 0.5°		RMS MAX.	
MATERIAL		REV 003	
FINISH	SEE NOTES	SCALE	ALIO STD TEMPLATE - REV 006
			1 OF 1

NOTE: MODEL AI-CM-15000-XY SHOWN.

NOTE: THRU HOLE AND TAP MOUNTING FEATURES (I, J, & K) ARE PRESENT ON TOP AND BOTTOM MOUNTING SURFACES EVEN THOUGH DIMENSIONS ARE ONLY SHOWN ON ONE SURFACE.