

ANR31

Technical Specifications

Technology	
travel mechanism	inertial piezo drive
positioner type	rotator
Size and Dimensions	
footprint; height	∅10; 7.5mm
aperture	0.6 mm
weight	g
Materials	
positioner body	titanium (upgrade option: copper beryllium)
actuator	PZT ceramics
connecting wires	insulated twisted pair, copper
Options	
environmental options	/RT
Load (@ ambient conditions)	
maximum load	0.05 N
maximum dynamic torque around axis	0.03 Ncm
maximum torque perpendicular to axis	1 Ncm
Coarse Positioning Mode	
input voltage range	0 - 60 V
travel range (step mode)	360 °
maximum drive velocity @ 300 K	approx. 3 °/s
typical minimum step size @ 300 K	1 m°
typical minimum step size @ 4 K	0.5 m°

Fine Positioning Mode	
fine positioning resolution	μ°
fine angular positioning range @ 300 K	40 m°
fine angular positioning range @ 4 K	8 m°
input DC voltage range @ 300 K	0 - 60 V
input DC voltage range @ 4 K	0 - 150 V
Accuracy of Movement	
repeatability of step sizes	typically 5 % over full range
typ. forward / backward step asymmetry	typically 5 %
Working Conditions	
mounting orientation	axis vertical
magnetic field range	0 - 31 T
minimum pressure (/RT)	ambient
temperature range (/RT)	273K .. 373K
Connectors and Feedthroughs	
cable	30 cm cable with connector
connector type	2-pole pin plug, ∅ 0.5 mm, d = 2 mm
electrical feedthrough solution	VFT/LT
Versions	
/RT version	1004583

Technical Drawings

