

# ANSz100lr

## Technical Specifications

Technology	
travel mechanism	piezo driven lever arm mechanism
positioner type	Scanner
Size and Dimensions	
footprint; height	24x24; 10mm
max installation space	24x24; 12mm
weight	g
Materials	
positioner body	titanium (upgrade option: copper beryllium)
actuator	PZT ceramics
connecting wires	insulated twisted pair, copper
Options	
environmental options	/RT
Load (@ ambient conditions)	
maximum load	1 N
Fine Positioning Mode	
fine positioning resolution	sub-nm
fine linear positioning range @ 300 K	50 $\mu$ m
fine linear positioning range @ 4 K	30 $\mu$ m
input DC voltage range @ 300 K	0 - 60 V
input DC voltage range @ 4 K	0 - 150 V
typical actuator capacitance fine @ 300 K	5.55 $\mu$ F
typical actuator capacitance fine @ 4 K	1.75 $\mu$ F

Accuracy of Movement	
repeatability of step sizes	no coarse positioning capability
scan repeatability	0.1 %
typ. forward / backward step asymmetry	no coarse positioning capability
creep	typically 0.5 - 0.8 % per decade of time
linearity	typically 5 - 10 %
Working Conditions	
magnetic field range	0 - 31 T
minimum pressure (/RT)	ambient
temperature range (/RT)	273K .. 373K
Connectors and Feedthroughs	
cable	30 cm cable with connector
connector type	2-pole pin plug, $\varnothing$ 0.5 mm, d = 2 mm
electrical feedthrough solution	VFT/LT
Versions	
/RT version	1005227

## Technical Drawings

