

# ECGp5050

## Technical Specifications

Technology	
travel mechanism	inertial piezo drive
positioner type	goniometer
Size and Dimensions	
footprint; height	50x50; 17mm
max installation space	50x69.8; 19.5mm
distance center of rotation to bottom	94 mm
weight (aluminium version)	137 g
weight (stainless steel version)	247 g
Materials	
positioner body	Aluminum
positioner body (/HV, /UHV)	stainless steel
actuator	PZT ceramics
connecting wires	copper, jacket: RT: silicon, HV/UHV: fiberglass
bearings	stainless steel
Options	
environmental options	/RT
Load (@ ambient conditions)	
maximum load	10 N
maximum dynamic torque around axis	7 Ncm
Coarse Positioning Mode	
input voltage range	0 - 60 V
travel range (step mode)	10 °
maximum drive velocity @ 300 K	3 °/s
typical minimum step size @ 300 K	0.1 m°

Fine Positioning Mode	
fine positioning resolution	μ°
fine angular positioning range @ 300 K	1.1 m°
input DC voltage range @ 300 K	0 - 100 V
Accuracy of Movement	
repeatability of step sizes	typically 5 % over full range
typ. forward / backward step asymmetry	10 %
Working Conditions	
mounting orientation	arbitrary
minimum pressure (/RT)	ambient
minimum pressure (/UHV)	1E-9 mbar
temperature range (/RT)	273K .. 373K
Connectors and Feedthroughs	
cable	50 cm cable with connector
connector type	14-pole connector
connector type (/HV, /UHV)	15-pin D-Sub connector
Versions	
/RT version	1006222

## Technical Drawings

