

series ENV 40 compact

voltage amplifier 40mA

The module ENV 40 C of the ENV series combines the excellent features of the ENV system with the compactness of the new 12V40 modules. The compact ENV series is very suitable for automated positioning and scanning applications in labs and industry where the direct display of the output values is not needed. All the drive signals can be tapped from the front plate as well as from the rear wiring.

The ENV 40 C module is available with integrated controller for the use of different position measurement systems on request. A PID controller is used for the position control.

A very compact attachable printed circuit board processes the analog signals of the sensor. This additional printed circuit board is also available separately, as well as for systems without measurement systems and systems with integrated capacitive or strain gauge measurement systems.



Image: module ENV 40 CSG

product highlights:

- amplifier for low voltage piezo elements
- multi channel system
- excellent cost effectiveness
- closed loop system integrated (option)

applications:

- automation systems
- driving piezoelements
- space-saving format
- OEM-applications



Tel: +49 (3641) 66880 • Fax: +49 (3641) 668866 info@piezosystem.com • http://www.piezosystem.de



series ENV 40 compact

technical details

	unit	ENV 40 C	ENV 40 CSG
part. no.		E-104-00	E-104-10
type of sensor controller	-	-	strain gauge
module width	HP	6	
output voltage range	V	-10 to +150	
output current (permanent)	mA	40	
voltage noise (absolute)	mV_{RMS}	<0.3 @500 Hz	
modulation input*	V	0 to +10	
input resistance	kΩ	10	
DC offset	-	³ ⁄4 turn potentiometer	
display	-	without display	
output connector	-	LEMO 0S.302	
sensor output	-	-	LEMO 0S.304
monitor output**	V	-1 to +15	0 to +10
output resistance	kΩ	100	1
connector MOD/MON		SMB connector	

* SMB plug available with part no. Z-006-70 (please see chapter "accessories")

** In open loop systems the output voltage is displayed in a 10:1 (-1 to 15V) ratio. In closed loop systems the edited sensor signal is available. The monitor output voltage is 0 to 10V for 100% motion in closed loop mode.



Tel: +49 (3641) 66880 • Fax: +49 (3641) 668866 info@piezosystem.com • http://www.piezosystem.de